




外徑
Ma. 材質 SUJ2

Tr. 處理 高週波

Ha. 硬度 HRC58

內徑
Ma. 材質 銅鈦合金

STA, STAA

STB, STBB

品 號			D	單 價	品 號			D	單 價	L						
Type	d				Type	d										
STA	13	+0.010 +0.004	22	+0.017 +0.008	•	STAA	13	+0.010 +0.004	22	±0.002	•	16	19	22	25	—
	16	+0.010 +0.004	25	+0.017 +0.008	•		16	+0.010 +0.004	25	±0.002	•	16	19	22	25	—
	19	+0.012 +0.006	28	+0.017 +0.008	•		19	+0.012 +0.006	28	±0.002	•	—	19	22	25	—
	22	+0.012 +0.006	35	+0.020 +0.009	•		22	+0.012 +0.006	35	±0.002	•	—	—	22	25	28

品 號			D	H	單價	品 號			D	H	單價	L						
Type	d					Type	d											
STB	13	+0.010 +0.004	22	+0.017 +0.008	28	•	STBB	13	+0.010 +0.004	22	±0.002	28	•	16	19	22	25	—
	16	+0.010 +0.004	25	+0.017 +0.008	31	•		16	+0.010 +0.004	25	±0.002	31	•	16	19	22	25	—
	19	+0.012 +0.006	28	+0.017 +0.008	34	•		19	+0.012 +0.006	28	±0.002	34	•	—	19	22	25	—
	22	+0.012 +0.006	35	+0.020 +0.009	41	•		22	+0.012 +0.006	35	±0.002	41	•	—	—	22	25	28

注意

- STA、STAA、STB、STBB和GPP、LLPM、SLPM、LPA、LPM……等配合使用
- 銅鈦合金導套以厭氧膠(P.872)黏著固定
- 高速導柱、導套、滾珠套專用之有機鉬強力潤滑劑請參考P.860

訂貨方式: 品 號 × L 交期: 1 天 STA, STB

STA13 × 16

20 天 STAA, STBB